

Product Data Sheet

Breyden Products, Inc. 71 E. Radio Road Columbia City, IN 46725 Phone: 260-244-2995

Product and Description

Part Number: GT750MW

Description: Medium weave woven fiberglass tape manufactured from high quality

electrical grade continuous filament fiberglass yarns. Breyden Products'

woven glass tapes are manufactured in an ISO9001 facility.

Additional Information: Breyden Products' woven fiberglass tapes are primarily used in

electrical applications as coil wraps, insulation, mechanical

reinforcements and other applications requiring high heat resistance. These tapes retain 50% of their tensile strength at 340 degrees C and is considered a Class H material. All tapes can be manufactured with

a center reference line.

Treatments Available (combinations of the options below are also

available).

Treatment Suffix:

ET - Fiberglass tape edges have been treated with a resin to

eliminate fraying and loose fibers

FIN111 - Fiberglass tape has been heat treated to remove yarn sizing. Heat treatment improves varnish impregnation and eliminates

fraving.

WS - Fiberglass tape has been weave set. This process eliminates

loose fibers and fraying. Weave setting produces a fiberglass tape

that is yellow in color.

Attributes

Width: .50"

Thickness: .007"

Tensile Strength (Minimum): 170 LBS.

Standard Color(s): Natural