



OVER SURFACE SPACING  
(CREEP DISTANCE) = 1.875"

B

B

A

A

<b>AVAILABLE THREADS</b>		
<b>UNC THREAD STYLES</b>		
<b>PART NUMBER</b>	<b>INSERT SIZE</b>	<b>MATERIAL</b>
R4175-A3	5/16-18 X 3/8	ALUMINUM
R4175-A4	3/8-16 X 3/8	ALUMINUM
R4175-S4	3/8-16 X 3/8	STEEL
<b>METRIC THREAD STYLES</b>		
R4175-A3/M8	M8 X 1.25 X 9.5	ALUMINUM
R4175-A4/M10	M10 X 1.50 X 9.5	ALUMINUM
R4175-S4/M10	M10 X 1.50 X 9.5	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

**CONFIDENTIAL**  
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



**MAR-BAL, Incorporated**  
5400 Reserve Way  
Dublin, VA 24084  
www.mar-bal.com

<b>TITLE</b>	
<b>4000 SERIES ROUND INSULATORS</b>	
<b>PART NUMBER:</b>	<b>SUGGESTED INDOOR RATING:</b>
<b>R4175-XX</b>	<b>2.0 kV</b>
<b>SHEET 1 OF 1</b>	<b>SCALE 1.000</b>