

# Glyptal Inc.

305 Eastern Avenue  
Chelsea, Massachusetts 02150

Telephone (617) 884-6918  
Fax (617) 884-8376

## PRODUCT DATA SHEET G3415

### DESCRIPTION

GLYPTAL G3415 is a specially-developed, durable enamel for finishing machinery and electrical apparatus to be operated outdoors. Equally suitable for interior use. May be used on primed wood or wood surfaces.

### WET SAMPLE

% Vol. Solids (avg.)	40
% Wt. Solids (avg.)	55
Viscosity	67-77 KU
Coverage (1 mil dry film thickness)	600-700 ft <sup>2</sup> /gal
Flashpoint, open cup	105 °F
Weight per Gallon (avg.)	9.0 lb/gal
Fineness of Grind (Hegman)	7 minimum
Solvent	Aliphatic/Aromatic

### APPLICATION

Substrate	Ferrous metal primed with G7635
Method	Spray, brush, or roller
Reducer	Xylol (G3190) for spray; Mineral spirits (G2085) for brush or roller

### CURE

Drying time, tack free	6 h
Handle	12 h
Recoat	16 h

### DRY FILM PROPERTIES

Color	#61 ASA Gray
Gloss, 60°	85+
Pencil Hardness	2B
Flexibility 1/8" mandrel	Pass 180°
Impact Resistance	
Direct	36 in-lb
Indirect	36 in-lb
Adhesion, Cross Hatch	Excellent

In as much as Glyptal, Inc. has no control over the use to which others put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material and the compositions described herein should make his or her own

tests to determine the materials' suitability for his or her own particular use. Statements concerning possible or suggested uses of the material described herein are not to be construed as constituting a license under any Glyptal patent covering such use or as recommendations for use of such materials in the infringement of any patent.