



Lectromat, Inc.

Electrical Insulation Specialties

P.O. BOX 608 Mars, Pennsylvania 16046

Phone: (724) 625-3502

Fax: (724) 625-2488

PRODUCT BULLETIN BANDING EDGE GUIDE

DESCRIPTION: Banding edge guide is constructed from .007" woven fiberglass cloth wrapped around various diameters of fiberglass roving. The cloth is sewn together to hold the roving in place.

APPLICATION: Banding edge guides are used extensively in DC traction to aid in the banding of armatures. BEG is wrapped around the armature and insures uniformity of glass banding tape. BEG is untreated and is compatible for use with VPI and static dip resins.

AVAILABILITY:	<u>Size</u>	<u>Bead</u>	<u>Width</u>
	1	5/16"	3"
	2	5/16"	1 1/2"
	3	1/4"	2"
	4	3/16"	4"
	5	3/16"	1 1/2"
	6	5/32"	1 1/4"
	7	5/32"	1"
	8	3/32"	1"
	9	3/32"	1 1/2"
	10	1/4"	1 1/2"
	11	3/32"	2"
	12	1/4"	3"
	13	5/32"	1 1/2"
	14	3/16"	1"
	15	3/16"	2"

Banding Edge Guide 060597 ORIG.

The information contained herein is intended to assist customers in determining whether our products are suitable for their application. Since we have no control over how our products are used, we cannot guarantee the performance of these products. We request that customers inspect and test our products before use and satisfy themselves as to suitability. The exclusive remedy for all proven claims is replacement of our material and in no event shall we be liable for special, incidental or consequential damages.