



OVER SURFACE SPACING  
(CREEP DISTANCE) = 3.50"

**AVAILABLE THREADS**

**UNC THREAD STYLES**

PART NUMBER	INSERT SIZE	MATERIAL
5300-A5	3/8-16 X 9/16	ALUMINUM
5300-S5	3/8-16 X 9/16	STEEL
5300-A6	1/2-13 X 5/8	ALUMINUM
5300-S6	1/2-13 X 5/8	STEEL
5300-S8	5/8-11 X 3/4	STEEL

**METRIC THREAD STYLES**

5300-A5/M10	M10 X 1.50 X 14.2	ALUMINUM
5300-S5/M10	M10 X 1.50 X 14.2	STEEL
5300-A6/M12	M12 X 1.75 X 15.8	ALUMINUM
5300-S6/M12	M12 X 1.75 X 15.8	STEEL
5300-S8/M16	M16 X 2.00 X 15.8	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

**CONFIDENTIAL**  
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 04-AUG-2008



**MAR-BAL, Incorporated**  
5400 Reserve Way  
Dublin, VA 24084  
www.mar-bal.com

TITLE <b>5000 SERIES OCTAGON INSULATOR</b>	
PART NUMBER: <b>5300-XX</b>	SUGGESTED INDOOR RATING: <b>4.1 kV</b>
SHEET 1 OF 1	SCALE 1.000