

Digital Multimeter

True RMS with backlist display

Features:

- ➔ Measurement functions include AC/DC Voltage and Current, Resistance, Capacitance, Frequency, Temperature & AC Bandwidth
- ➔ Relative, Min/Max, Peak Hold & Zoom
- ➔ Smart Auto Power Off
- ➔ Complete with Built-In Stand, Test Leads, Protective Holster, 9V Battery, & Bead Wire Temperature Probe

Ranges:

- AC/DC Voltage: .01 mV to 1,000 V
- AC/DC Current: .01 μ A to 20 A
- Resistance (Ω): .01 to 50 M
- Capacitance: 0.01 nF to 9999 μ F
- Frequency: 10 Hz to 125 kHz
- Temperature: -58° to 1,832° F
-50 C to 1,000 C
- AC Bandwidth: 40 Hz to 20 kHz
- CAT IV-600V
- CE/UL Listed



	Catalog Number
Digital Multimeter	VAOTMP530
Net Weight 0.75 Lb. (340g), Shipping Weight 2 Lbs.	

Dimensions:
7.32" x 3.42" x 1.39"
(186 x 87 x 35.5 mm)

V.A.O. Testers

Simpson Models 260-8 and 260-8P



Features:

- ➔ **Model 260-8** — world famous; offers movement overload protection, input protection, increased stability, and self-shielded meter movement.
- ➔ **Model 260-8P** — is identical to Model 260-8, but with built-in meter and tester protection approaching 100% which makes this instrument virtually GOOF-PROOF. A reset button pops out indicating overload. Circuits cannot be reset while the overload is present. This is especially important for inexperienced operators.

Mirrored Scale

UL Listed

Dimensions:
5-1/4" x 7" x 3-1/8"

Ranges:

- Volts, D.C.: 0-0.250, 1, 2.5, 10, 50, 250, 500, 1000.
- Volts, A.C.: 0-2.5, 10, 25, 50, 250, 500, 1000.
- Amperes, D.C.: 0-10 (250 MV Drop).
- Amperes, A.C.: up to 250 amperes in 6 ranges with Model 150-2 Amp-Clamp.
- Milliamperes, D.C. only: 0-1, 10, 100, 500.
- Ohms: Rx1 0-2000 (12 Ω center)
- Rx100 0-200,000 (1,200 Ω center)
- Rx10,000 0-20 megohms (120,000 Ω center)
- dB Scale, (IMW 600 ohms) - 20 to + 10, - 8 to + 22,
+ 6 to + 36, + 20 to + 50.

	Catalog Number
Model 260-8 complete with leads	VAOT2608
Model 260-8P complete with leads	VAOT2608P
Net Weight 3-1/2 Lbs., Shipping Weight 5 Lbs.	
Carrying Case for either of above	VAOT260C



MARTINDALE • PO Box 430 • Cleveland, OH 44107
 Phone (216) 521-8567 • Fax Local 521-9476 / USA & Canada (800) 344-9191
 E-Mail: sales@martindaleco.com
 Web Site: www.martindaleco.com